



## COGGED SIZES

### 3VX HY-T<sup>®</sup> WEDGE BELTS: Top Width = 0.38" Thickness = 0.31"

BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB	BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB	BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB
3VX250	25.0	.11	3VX475	47.5	.20	3VX900	90.0	.37
3VX265	26.5	.11	3VX500	50.0	.21	3VX950	95.0	.39
3VX280	28.0	.12	3VX530	53.0	.22	3VX1000	100.0	.41
3VX300	30.0	.13	3VX560	56.0	.23	3VX1060	106.0	.44
3VX315	31.5	.13	3VX600	60.0	.25	3VX1120	112.0	.46
3VX335	33.5	.14	3VX630	63.0	.26	3VX1180	118.0	.49
3VX355	35.5	.15	3VX670	67.0	.28	3VX1250	125.0	.58
3VX375	37.5	.16	3VX710	71.0	.29	3VX1320	132.0	.61
3VX400	40.0	.17	3VX750	75.0	.31	3VX1400	140.0	.65
3VX425	42.5	.18	3VX800	80.0	.33	3VX1500	150.0	.62
3VX450	45.0	.19	3VX850	85.0	.35			

### 5VX HY-T<sup>®</sup> WEDGE BELTS: Top Width = 0.62" Thickness = 0.53"

BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB	BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB	BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB
5VX450	45.0	.44	5VX680	68.0	.66	5VX1000	100.0	.97
5VX470	47.0	.46	5VX690	69.0	.67	5VX1030	103.0	1.00
5VX490	49.0	.48	5VX710	71.0	.69	5VX1060	106.0	1.03
5VX500	50.0	.49	5VX730	73.0	.71	5VX1080	108.0	1.04
5VX510	51.0	.50	5VX740	74.0	.72	5VX1120	112.0	1.08
5VX530	53.0	.52	5VX750	75.0	.73	5VX1150	115.0	1.11
5VX540	54.0	.53	5VX780	78.0	.76	5VX1180	118.0	1.14
5VX550	55.0	.54	5VX800	80.0	.78	5VX1230	123.0	1.46
5VX560	56.0	.55	5VX810	81.0	.79	5VX1250	125.0	1.49
5VX570	57.0	.56	5VX830	83.0	.81	5VX1320	132.0	1.58
5VX580	58.0	.57	5VX840	84.0	.82	5VX1400	140.0	1.67
5VX590	59.0	.58	5VX850	85.0	.83	5VX1500	150.0	1.79
5VX600	60.0	.59	5VX860	86.0	.84	5VX1600	160.0	1.91
5VX610	61.0	.60	5VX880	88.0	.85	5VX1700	170.0	2.02
5VX630	63.0	.62	5VX900	90.0	.87	5VX1800	180.0	2.14
5VX650	65.0	.64	5VX930	93.0	.90	5VX1900	190.0	2.26
5VX660	66.0	.64	5VX950	95.0	.92	5VX2000	200.0	2.38
5VX670	67.0	.65	5VX960	96.0	.93			